


Type of Appliance	Commercial Condensing Tankless Water Heater, Commercial Energy Star Qualified
Rinnai model number	REU-KB3237WDC-US
Operation / Installation	Forced combustion; outdoor only
Minimum/Maximum Gas Rate (Input)	15,200 - 199,000 BTU/h (4.5-58.3 kWh)
Electrical	Appliance: AC 120 Volts - 60 Hz Temperature Controller: DC 12 Volts
Electrical Consumption	Normal: 71 w Standby: 2 w Anti-frost protection: 168 w
Amperage	Max: 4A
Ignition System	Direct electronic ignition
Hot Water Capacity	Minimum flow rate: 0.26 GPM (1 l/min) Minimum activation flow rate: 0.4 GPM (1.5 l/min) Maximum flow rate: 9.8 GPM (37.1 l/min)
Temperature	Factory Default Range - 98°-120° F (37°- 49°C) Optional Range - 98° - 185° F (37°- 85°C)
Temperature (without remote)	120° F 49°C (factory default) or 140° F (60°C)
Approved Gas Types	Natural or Propane (ensure unit matches gas type)
Thermal Efficiency	Natural Gas: 96% Propane: 96%
Service Connections	Gas supply: 3/4 inch (19mm) MNPT Cold water inlet: 3/4 inch (19mm) MNPT Hot water outlet: 3/4 inch (19mm) MNPT
Isolation & Pressure Relief Valves Included	Isolation Valves are certified to NSF/ANSI 61 for potable water
Water Flow Control	Water flow sensor, electronic water control and by-pass control
Minimum/Maximum Water Supply Pressure	20 - 150 PSI (138-1035 KPa) (recommended 60 - 80 PSI (414 - 552 KPa) for optimal performance)

Rinnai is continually updating and improving products; therefore, specifications are subject to change without prior notice. Local, state, provincial and federal codes must be adhered to prior to installation.



Controller

MC-91-2US (included)

Controller Cable

Non-polarized two-core cable, minimum 22 AWG

Safety Devices

- Flame failure - Flame Rod
- Boiling protection
- Combustion fan rpm check
- Over current - glass fuse
- Remaining flame (OHS)
- Thermal fuse
- Automatic frost protection

Clearances from Combustibles

- Top of heater - 12 inches (305mm)
- Front (Panel) - 24 inches (610mm)
- Front (Exhaust) - 24 inches (610mm)
- Back of heater - 0 inches
- Bottom of heater - 12 inches (305mm)
- Sides of heater - 6 inches (152mm)

Clearances from Non-combustibles

* 24 inches (610mm) required for service

- Top of heater - 2 inches (51mm)
- Front (Panel) - 0 inches *
- Front (Exhaust) - 24 inches (610mm)
- Back of heater - 0 inches
- Bottom of heater - 2 inches (51mm)
- Sides of heater - 1/8 inch (3.2mm)

Min. / Max. Gas Supply Pressure

Natural Gas: min 4" W.C. (2.5mbar) max 10.5" W.C. (26.1mbar)
 Propane Gas: min 8" W.C. (20mbar) max 13.5" W.C. (33.6mbar)

Manifold Gas Pressure (inches W.C.)

Natural Gas: high fire 3.1" W.C. (7.7mbar) low fire 0.51" W.C. (1.3mbar)
 Propane Gas: high fire 3.7" W.C. (9.2mbar) low fire 0.52" W.C. (1.3mbar)

NOx

Complies with South Coast Air Quality Management District 14 ng/J or 20 ppm NOx emission levels

Limited Warranty

Heat exchanger: 6 years*, All other parts: 5 years*; Labor: 1 year;
 (* 3 years if used as a circulating water heater within a circulation loop, when the water heater is in series with a circulation system and all circulating water flows through the water heater, and where an aquastat / thermostat, timer, or an on-demand recirculation system is not incorporated.)
 Refer to the manual for complete warranty information.

